

HR150



Heat Regenerated Dehydrator, 19 in rack mountable, 3.0 kPa (0.44 psig), with summary alarms, 48 Vdc (ac operation possible using optional power supply purchased separately)

Product Classification

Product Type Dehydrator

General Specifications

Alarm Type	Summary
Cut In/Out Pressure Type	Continuous (default set to 3.0 kPa 0.4 psig)
Dehydrator Type	Automatically regenerating Desiccant
Flow Rate, nominal	2.5 SLPM
High-Pressure Alarm	Factory set (default set to 4.5 kPa 0.7 psig)
Low-Pressure Alarm	Factory set (default set to 1.5 kPa 0.22 psig)
Mounting	Rack
Port Count	4
Port Type	3/8 in PE tube
Power Cord	dc power cord
Rack Type	EIA 19 in ETSI N3 (optional)
Rack Units	2
Regulated Output Pressure Type	factory set, continuous

Dimensions

Product Height	91.8 mm 3.614 in
Product Width	439.4 mm 17.299 in
Product Depth	190.5 mm 7.5 in
Volume Capacity, maximum	0.6 m ³ 21.189 ft ³

HR150

Outline Drawing–Front

HR150

Outline Drawing–Side

HR150

Outline Drawing–Back

HR150

Outline Drawing–Top

Electrical Specifications

Alarm Contact Rating	Handles at least 0.5 A (ac or dc)
Power Consumption, maximum	45 W
Voltage	48–60 Vdc \pm 10%
Voltage Type	dc

Environmental Specifications

Operating Temperature	-5 °C to +50 °C (+23 °F to +122 °F)
------------------------------	-------------------------------------

Packaging and Weights

HR150

Weight, gross 9.6 kg | 21.164 lb

Weight, net 4.8 kg | 10.582 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted

