

19256B

Lace-up Hoisting Grip for 7/8 in coaxial cable, elliptical waveguide 77, and HELIAX® FiberFeed® Hybrid cable



Product Classification

Product Type	Hoisting grip
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Attachment Spacing Intervals	200 ft 60.96 m
Hoisting Grip Type	Lace-up hoisting grip
Support Clamp	Not included
Tool Type	Hoisting grip

Dimensions

Grip Length, minimum	17 in 431.8 mm
Leader Length, minimum	13 in 330.2 mm
Nominal Size	7/8 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

Mechanical Specifications

Pull Load Capacity	500 lb 226.796 kg
---------------------------	---------------------

Packaging and Weights

19256B

Height, packed	1.5 in 38.1 mm
Width, packed	8.6 in 218.44 mm
Length, packed	8.7 in 220.98 mm
Packaging quantity	1
Weight, gross	0.22 kg 0.485 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

