

# 223700-724

---



Standard Grounding Kit for 2-1/4 in and 3 in corrugated coaxial cable and elliptical waveguide 28 and 37

## Product Classification

<b>Product Type</b>	Grounding kit
<b>Ordering Note</b>	CommScope® non-standard product

## General Specifications

<b>Bonding Conductor Jacketing Material</b>	PVC
<b>Bonding Conductor Material</b>	Copper
<b>Bonding Conductor Wire Size</b>	6 gauge
<b>Cable Type</b>	Corrugated   Elliptical waveguide
<b>Color</b>	Black
<b>Grounding Kit Type</b>	Standard Grounding Kits
<b>Grounding Strap Material</b>	Copper
<b>Lug Attachment</b>	Field attached
<b>Lug Type</b>	Two-hole lug
<b>Thread Size</b>	3/8 in

## Dimensions

<b>Bonding Conductor Length</b>	60 in   1524 mm
<b>Cable Jacketing Removal Length, maximum</b>	2.3 in   58.42 mm
<b>Cable Jacketing Removal Length, minimum</b>	2.2 in   55.88 mm
<b>Compatible Diameter, maximum</b>	3.1 in   78.74 mm
<b>Compatible Diameter, minimum</b>	2.31 in   58.674 mm
<b>Nominal Size</b>	2-1/4 in   3 in
<b>Waveguide Size</b>	WR229   WG11   R40   WR284   WG10   R32

## Electrical Specifications

# 223700-724

---

<b>Current Handling</b>	Tested to withstand 100,000 amps peak current surge
<b>Current Handling Test Method</b>	MIL-STD-1757
<b>Grounding, Bonding and Shielding Test Method</b>	MIL-STD-188-124A
<b>Lightning Protection Test Method</b>	IEC 1024-1

## Material Specifications

<b>Rivet Material</b>	Copper
-----------------------	--------

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Storage Temperature</b>	-40 °C to +80 °C (-40 °F to +176 °F)
<b>Blowing Rain Test Method</b>	MIL-STD-810, Method 506
<b>Corrosion Test Method</b>	MIL-STD-1344, Method 1001
<b>Freezing Rain/Icing Test Method</b>	MIL-STD-810, Method 521
<b>Humidity Test Method</b>	MIL-STD-1344, Method 1002
<b>Immersion Test Method</b>	IEC 60529:2001, IP68
<b>UV Resistance Test Method</b>	MIL-STD-810, Method 505
<b>Vibration Test Method</b>	MIL-STD-202, Method 214
<b>Weatherproofing Method</b>	Butyl and electric tape

## Packaging and Weights

<b>Height, packed</b>	10.6 in   269.24 mm
<b>Width, packed</b>	2.3 in   58.42 mm
<b>Length, packed</b>	7 in   177.8 mm
<b>Included</b>	Grounding kit   Hardware   Lug   One roll of 2 in PVC tape   One roll of 24 in butyl rubber tape
<b>Packaging quantity</b>	1
<b>Weight, gross</b>	0.92 kg   2.028 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant



## Included Products

**42615-10** — Butyl Rubber Tape, 24 in

**9905-71** — Black 2 in PVC Tape, 20 ft

## \* Footnotes

**Grounding, Bonding and Shielding Test Method** Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm

**Lightning Protection Test Method** Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III–IV, 1995-02