



Butterfly Hanger for 5 in coaxial cable and elliptical waveguide 20

Product Classification

Product Type	Hanger kit
Ordering Note	CommScope® non-standard product

General Specifications

Cable Type	Corrugated
Cables per Hanger	1
Color	Silver
Hanger Type	Standard butterfly hanger
Mounting	1/2 in threads

Dimensions

Height	1.65 in 41.91 mm
Width	1.5 in 38.1 mm
Length	2.5 in 63.5 mm
Compatible Diameter, maximum	5.2 in 132.08 mm
Compatible Diameter, minimum	5 in 127 mm
Nominal Size	5 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Galvanized steel
----------------------	------------------

Mechanical Specifications

33598-5

Vibration Survival

≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature

-40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation

≥500 hours in salt spray chamber

Environmental Strength Capability

Double cable weight

Packaging and Weights

Height, packed

36.8 cm | 14.488 in

Width, packed

11 cm | 4.331 in

Length, packed

11 cm | 4.331 in

Packaging quantity

10

Weight, gross

2.11 kg | 4.652 lb

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

REACH-SVHC

ROHS

Classification

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

