


43211A



Butterfly Hanger for 1/2 in or 3/8 in coaxial cable and elliptical waveguide 180, 220, and 240

Product Classification

Product Type

Hanger kit

Ordering Note

CommScope® standard product in Mexico, Central America, and South America | CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger

1

Color

Silver

Hanger Type

Standard butterfly hanger

Mounting

3/8 in (M10) drilled cable ladder

Dimensions

Height

1.25 in | 31.75 mm

Width

1.5 in | 38.1 mm

Length

1.6 in | 40.64 mm

Compatible Diameter, maximum

0.64 in | 16.256 mm

Compatible Diameter, minimum

0.41 in | 10.414 mm

Nominal Size

1/2 in

Electrical Specifications

Return Loss Effect

0.1 dB

DTF Effect

0.1 dB

Material Specifications

Material Type

Stainless steel

43211A

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

Height, packed 14.8 cm | 5.827 in

Width, packed 10.6 cm | 4.173 in

Length, packed 9 cm | 3.543 in

Packaging quantity 10

Weight, gross 0.34 kg | 0.75 lb

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

