

# 6600D-4

---

4-port Distribution Manifold, wall mountable, 0–15.0 psig, 25 ft of tubing per port

## Product Classification

**Product Type** Manifold

## General Specifications

**Distribution System** Manifold  
**Mounting** Wall  
**Port Count** 4  
**Port Type** 3/8 in PE tube  
**Regulated Output Pressure, maximum** 15 psig | 103.421 kPa  
**Regulated Output Pressure, minimum** 0 psig | 0 kPa

## Dimensions

**Product Height** 6.5 in | 165.1 mm  
**Product Width** 11 in | 279.4 mm  
**Product Depth** 2.5 in | 63.5 mm

## Environmental Specifications

**Operating Temperature** +1 °C to +40 °C (+33 °F to +104 °F)

## Packaging and Weights

**Height, packed** 16 in | 406.4 mm  
**Width, packed** 7 in | 177.8 mm  
**Depth, packed** 22 in | 558.8 mm  
**Included** 3/8 in polyethylene tubing | 90° elbow fitting | Cable tie | Male connector fitting | PTFE tape  
**Weight, gross** 3.63 kg | 8.003 lb

# 6600D-4

---

**Weight, net**

2.76 kg | 6.085 lb

## Regulatory Compliance/Certifications

**Agency**

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

**Classification**

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

Compliant

