

EW220, HELIAX® Standard Elliptical Waveguide, 21.2–23.6 GHz, black PE jacket

Product Classification					
Product Type	Elliptical waveguide				
Product Brand		HELIAX®			
General Specifications					
Jacket Color		Black			
Performance Note	Verformance Note Va		Values typical, unless otherwise stated		
Dimensions					
iameter Over Jacket (E Plane) 17.8 mm 0.701 in					
Diameter Over Jacket (H Plane)		11.2 mm 0.441 in			
Cable Volume		74 L/km 0.798 ft³/kft			
Electrical Specifications					
Attenuation, Ambient Temperature		75 °F 23.889 °C			
eTE11 Mode Cutoff 13.338 GHz					
Group Delay at Frequency	127 ns/100 ft @ 22.400 GHz 415 ns/100 m @ 22.400 GHz				
Operating Frequency Band		21.2 – 23.6 GHz			
VSWR/Return Loss					
Frequency Band	VSWR	Return Loss (dB)			
21.2–23.6 GHz	1.15	23.13			
Attenuation					
Frequency (GHz)	Attenuation (dB/100 m	a) Attenuation (dB/100 ft)	Average Power (kW)	Group Velocity %	
21.2	28.042	8.547	0.398	77.7	
21.6	27.799	8.473	0.401	78.7	

Page 1 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 15, 2020



EW220

22.0	27.577	8.406	0.404	79.5
22.4	27.376	8.344	0.407	80.3
22.8	27.192	8.288	0.41	81.1
23.2	27.024	8.237	0.413	81.8
23.6	26.87	8.19	0.415	82.5

Material Specifications

Conductor Material	Corrugated copper	
Jacket Material	PE	
Mechanical Specifications		
Minimum Rond Padius, Multiple Ronds (E Plane)	120 mm 1721 in	

Minimum Bend Radius, Multiple Bends (E Plane)	120 mm 4.724 in
Minimum Bend Radius, Multiple Bends (H Plane)	230 mm 9.055 in
Minimum Bend Radius, Single Bend (E Plane)	120 mm 4.724 in
Minimum Bend Radius, Single Bend (H Plane)	230 mm 9.055 in
Maximum Twist	2 °/ft 6.562 °/m

Environmental Specifications

Installation temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)	
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)	
Average Power, Ambient Temperature	104 °F 40 °C	
Average Power, Temperature Rise	42 °C 107.6 °F	

Packaging and Weights

Cable weight

0.18 kg/m | 1.302 lb/ft

Regulatory Compliance/Certifications

Classification

Agency

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system



Page 2 of 2

